

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 172 207 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

16.01.2002 Bulletin 2002/03

(51) Int Cl.7: B41F 30/04

(21) Application number: 01114549.7

(22) Date of filing: 18.06.2001

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 12.07.2000 JP 2000210987

(71) Applicant: KABUSHIKI KAISHA TOKYO KIKAI
SEISAKUSHO

Tokyo 108-0014 (JP)

(72) Inventors:

- Yoshizawa, Kohji
Kawasaki-shi, Kanagawa (JP)
- Yoneta, Mutsuhito
Tokyo (JP)
- Hachiya, Tadashi
Yokohama-shi, Kanagawa (JP)

(74) Representative: Schmitt, Armand

Office Ernest T. Freylinger S.A., B.P. 48
8001 Strassen (LU)


(54) Blanket cylinder providing for ready mounting and dismounting of a blanket

(57) A blanket cylinder for use in offset lithography in combination with a blanket assembly (T) including a blanket (28) and a carrier sheet (C) therefor. The carrier sheet of the blanket assembly has a major portion (20) to which the blanket is attached, a first flange (21) at an acute angle to the major portion, a second flange (27) at an obtuse angle to the major portion and a rim (23) at an acute angle to the second flange. The blanket cylinder comprises a cylinder assembly (B) having formed therein an undercut groove (7) with an entrance slot (6) bounded by and between a first (24) and a second (25) longitudinal edge, the first longitudinal edge being cross-sectionally shaped to be engaged by the first flange (21) of the carrier sheet (C), and a retainer spindle

(12) mounted in the undercut groove in the cylinder assembly for bidirectional rotation therein.

In order to hold the blanket assembly (T) closely wrapped around the cylinder assembly (B), the retainer spindle (12) is cross-sectionally shaped to include a pull-in hook (16) for engaging the rim (23) of the carrier sheet (C) in order to pull the second flange (27) thereof into the undercut groove (7) with the rotation of the retainer spindle in a first direction, and a push-out ledge (28) for abutment against the rim (23) of the carrier sheet in order to push the second flange (27) out the undercut groove with the rotation of the retainer spindle in a second direction. The retainer spindle (12) is biased by a pair of torsion springs (17, 18) to turn in the first direction.

FIG. 1



Description

BACKGROUND OF THE INVENTION

[0001] This invention relates to printing presses, to web-fed offset printing presses, and, more specifically, to a blanket cylinder for use in such presses. Still more specifically, the invention deals with improvements in or relating to such a blanket cylinder designed for easy, firm mounting of a blanket around the same as well as for ready dismounting of the blanket therefrom.

[0002] In web-fed offset lithography, as is well known, a printing plate on a plate cylinder prints the inked image on the surface of a blanket of rubber or like material fastened to a blanket cylinder. The printed image is then offset or transferred from the blanket to the web running against an impression cylinder or, in offset perfecting presses, against another blanket cylinder.

[0003] A variety of blanket cylinders have been devised and used which are designed for easy mounting and dismounting of blankets. Out of such prior art devices, two are considered pertinent to the instant invention. One of these, disclosed in Japanese Unexamined Patent Publication No. 9-99543, teaches to create in a blanket cylinder an undercut groove extending parallel to the cylinder axis. Rotatably mounted in the undercut groove is a spring-loaded spindle having a series of pusher lugs aligned longitudinally thereof at constant spacings. The spindle is driven between a working position, in which the pusher lugs are oriented normal to the wall surface of the undercut groove, and a retracted position in which the lugs are turned away from the groove wall.

[0004] The rubber blanket for use with this prior art blanket cylinder is bonded to a sheet-metal carrier of rectangular shape. The blanket carrier has a pair of opposite end portions, extending beyond the edges of the blanket, that are bent respectively into an acute and an obtuse angle whose sum is approximately 180 degrees.

[0005] For mounting the blanket to the blanket cylinder, the acute-angled end portion of the blanket carrier is first hooked onto one of the pair of longitudinal edges of the entrance opening of the undercut groove; then the blanket with the carrier is wound around the cylinder by turning the latter; and then the obtuse-angled end portion of the blanket carrier is inserted in the undercut groove. The pair of opposite end portions of the blanket carrier, bent complementarily, are now held against each other in the undercut groove. Then the spring-loaded spindle is revolved from the retracted to the working position, with the result that the pusher lugs thereon are turned into abutment against the superposed end portions of the blanket carrier, until, with the blanket tightened against the cylinder, the pusher lugs become approximately perpendicular to the carrier end portions, pushing them against the groove wall and so frictionally retaining them against displacement during printing. The spindle is to be turned back to the retracted position

for dismounting the blanket.

[0006] An objection to this prior art blanket cylinder is the frictional engagement of the blanket carrier end portions by the pusher lugs on the spindle. During printing, of course, the blanket cylinder rotates in rolling engagement with the plate cylinder and, via the web of paper, with the impression cylinder or, in the case of an offset perfecting press, with the blanket cylinder on the other side of the web. The blanket tends to slacken and get loose on the blanket cylinder by reasons of its direct or indirect contact with the other cylinders. The prior art blanket cylinder is totally unequipped to take up the possible slack.

[0007] Japanese Patent No. 2,746,839 defeats the noted shortcoming of the first described prior art device, suggesting a blanket cylinder also having a groove cut in its surface so as to extend parallel to the cylinder axis. Rotatably received in this groove, a blanket-tightening spindle is toothed for mating engagement with racks each extending at right angles with the spindle axis and all arranged at spacings axially of the spindle. The racks are sprung, biasing the spindle to turn in a predetermined blanket-tightening direction.

[0008] The blanket for use with the second recited known blanket cylinder has a pair of metal-made mounting fixtures on its opposite ends. One of the fixtures is hooked onto one of the jaws bounding the longitudinal edges of the groove in the blanket cylinder. Then, after wrapping the blanket around the cylinder, the other fixture is inserted in the cylinder groove and further in a groove in the tightening spindle. Then the racks are driven by the springs to revolve the spindle in the tightening direction, until the blanket is held fast against the cylinder surface.

[0009] It is a definite advantage of this second known blanket cylinder that the blanket thereon is not to develop a slack during printing, because then the springs continue to energize the spindle in the blanket-tightening direction. This advantage is offset, however, by some inherent drawbacks.

[0010] First, the second prior art device requires an inconveniently wide groove in the blanket cylinder, wide enough to receive both ends of the blanket together with the mounting fixtures thereon. More precisely, the groove must be wider than the sum of twice the blanket thickness and the total thickness of the fixtures on its opposite ends. Considerable vibration and noise has therefore been generated when, during printing, the meeting ends of the blanket on the blanket cylinder come into direct forced engagement with the meeting ends of the printing plate on the plate cylinder or, via the web, with those of the other blanket on the other blanket cylinder. A reduction of mechanical vibration and noise is of utmost importance as printing presses today are designed to run faster and faster.

[0011] Another drawback concerns the complexity of the means for biasing the blanket-tightening spindle in one direction of rotation, such means comprising sets

of gear teeth formed on the spindle, racks engaged with the teeth, and compression springs acting on the racks. Additionally, an air conduit together with a source of air under pressure is needed for loosening the blanket by turning the spindle in the opposite direction against the forces of the compression springs.

SUMMARY OF THE INVENTION

[0012] It is therefore an object of this invention to provide a blanket cylinder so made that the blanket mounted thereto is to stay closely wrapped around the same against the risk of slacking during printing, assuring the production of high quality printings.

[0013] Another object of the invention is to attain the first recited object by creating in the blanket cylinder an undercut groove having an entrance slot of materially less width, with a view to the reduction of noise and vibration conventionally generated by reason of an inconveniently wide entrance slot.

[0014] Another object of the invention is to make the means for pulling the blanket, as the same is mounted to the blanket cylinder, so as to hold the blanket tightly around the blanket cylinder, far simpler and less expensive than heretofore.

[0015] A further object of the invention is to expedite the mounting and dismounting of the blanket to and from the blanket cylinder.

[0016] In summary, the present invention concerns an improved blanket cylinder for use in offset lithography, in combination with a blanket assembly which includes a blanket and a carrier sheet therefor. The carrier sheet of the blanket assembly has a major portion to which the blanket is attached, a first end portion bent at an angle to the major portion to provide a first flange, and a second end portion bent twofold to provide a second flange at an angle to the major portion, and a rim at an angle to the second flange.

[0017] The blanket cylinder comprises a cylinder having formed therein an undercut groove extending parallel to the axis of the cylinder. The undercut groove has an entrance slot bounded by and between a first longitudinal edge which is cross-sectionally shaped to be positively engaged by the first flange of the carrier sheet in mounting the blanket assembly to the cylinder, and a second longitudinal edge which is cross-sectionally shaped to be temporarily engaged by the rim of the carrier sheet preparatory to insertion of the second flange thereof into the undercut groove. Received in the undercut groove for bidirectional rotation therein, a retainer spindle is cross-sectionally shaped to include a hook for engaging the rim of the carrier sheet in order to pull the second end portion thereof into the undercut groove with the rotation of the retainer spindle in a first direction, and a ledge, circumferentially spaced from and opposed to the hook, for abutment against the rim of the carrier sheet in order to push the second end portion thereof out the undercut groove with the rotation of the retainer

spindle in a second direction opposite to the first. Also included is a resilient means for energizing the retainer spindle in the first direction relative to the cylinder in order to hold the blanket assembly fast against the cylinder.

[0018] Such being the improved construction of the blanket cylinder according to the invention, it is only the opposite end portions of the carrier sheet that are inserted in the undercut groove for mounting the blanket assembly to the blanket cylinder. The entrance slot of the undercut groove can therefore be as narrow as only somewhat more than twice the thickness of the carrier sheet, resulting in appreciable curtailment of the vibration and noise generated upon forced meeting of the slot with the slots of the neighboring cylinders in a web-fed offset printing press.

[0019] Upon completion of being mounted to the blanket cylinder, the blanket assembly has its first flange held hooked onto the first longitudinal edge of the entrance slot. The second flange of the blanket assembly is also received wholly in the undercut groove as the rim of the second flange, engaged by the hook of the retainer spindle, is thereby pulled into the groove under the force of the resilient means. The blanket assembly is thus to stay tightly wrapped around the blanket cylinder against the risk of slacking even when placed in forced rolling contact with the plate cylinder and, via the web, with the impression cylinder or another blanket cylinder, during printing.

[0020] In one embodiment of the invention, the resilient means biasing the retainer spindle in the blanket-tightening direction takes the form of a pair of torsion springs coiled around the opposite end portions of the retainer spindle. The retainer spindle with such resilient means can be compactly and inexpensively built into the blanket cylinder.

[0021] The dismounting of the blanket assembly from the blanket cylinder is just as easy as its mounting. The blanket assembly will come loose on the cylinder simply as the retainer spindle is turned against the bias of the resilient torsion springs, as then the ledge of the spindle will push the rim of the carrier sheet toward the entrance slot of the groove.

[0022] In order to expedite such dismounting of the blanket assembly without making the blanket cylinder any more complex in construction, the retainer spindle has a pair of aligned extensions of hexagonal cross section projecting from the opposite ends of the blanket cylinder. Either extension of the spindle may be manually turned by a wrench or spanner, readily available in any printing plant, against the forces of the torsion springs. The above and other objects, features and advantages of the invention and the manner of realizing them will become more apparent, and the invention itself will best be understood, from the following description taken together with the attached drawings showing the preferred embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023]

FIG. 1 is a side elevation of an example of blanket cylinder constructed in accordance with the present invention, the cylinder being shown partly broken away and partly shown in axial section to reveal, in particular, the undercut groove and the blanket retainer spindle received therein;

FIG. 2 is an enlarged, fragmentary cross section through the blanket cylinder, taken along the line II-II in FIG. 1, the view showing in particular how a blanket assembly has its opposite ends received in the undercut groove in the blanket cylinder, and one of them engaged by the retainer spindle;

FIG. 3 is a perspective view, partly broken away for illustrative convenience, of the blanket assembly for use with the FIG. 1 blanket cylinder;

FIGS. 4A through 4E are a series of diagrammatic cross-sectional views somewhat similar to FIG. 2 but explanatory of the FIG. 3 blanket assembly is mounted to the FIG. 1 blanket cylinder; and

FIGS. 5A through 5C are a series of diagrammatic cross-sectional views similar to FIGS. 4A-4E but explanatory of how the blanket assembly is dismounted from the blanket cylinder.

DESCRIPTION OF THE PREFERRED EMBODIMENT

General

[0024] In web-fed offset printing presses in general, the blanket cylinder and the plate cylinder are so angularly correlated to each other that the pair of meeting ends of a blanket on the blanket cylinder come into contact with the pair of meeting ends of a printing plate on the plate cylinder. Likewise, in an offset perfecting press having a pair of blanket cylinders for concurrently printing on both sides of the web, the pair of meeting ends of the blanket on one cylinder come into contact, via the web, with the pair of meeting ends of the blanket on the other cylinder. FIGS. 1 and 2 illustrate how each such blanket cylinder is constructed to retain the pair of meeting ends of a blanket in position thereon according to the novel concepts of this invention.

[0025] The capital B in both FIGS. 1 and 2 generally denotes a cylinder assembly having formed eccentrically therein an undercut groove 7 extending parallel to the cylinder axis. The undercut groove 7 has a relatively constricted entrance slot 6 cut in the surface of the cylinder assembly B. A blanket assembly T, shown by itself in FIG. 3, is to be mounted to the cylinder assembly B by having its pair of opposite ends engaged in the un-

dercut groove 7 through the entrance slot 6.

[0026] Rotatably received in the undercut groove 7 is a blanket retainer spindle 12 for positively engaging one end of the blanket assembly T. The retainer spindle 12 is spring biased to pull that end of the blanket assembly T deeper into the undercut groove 7 and hence to hold the blanket assembly tightly against the cylinder assembly B. At 13 are shown means for turning the retainer spindle 12 against the spring bias to loosen and dismount the blanket assembly T.

[0027] The noted blanket assembly T, cylinder assembly B, and blanket retainer spindle 12 will be discussed in more detail hereinbelow, in that order and under separate headings. How the blanket assembly T is mounted to, and dismounted from, the cylinder assembly B will be explained after the discussion of the listed major components.

Blanket Assembly

[0028] With reference to FIG. 3 the blanket assembly T is a combination of a blanket 26 of rubber or like material and a metal-made carrier sheet C therefor. The carrier sheet C has a major portion 20 to which the blanket 26 is bonded, a first end portion bent at an acute angle to the major portion 20 to provide a first flange 21, and a second end portion bent twofold at 22 and 29 to provide a second flange 27, which is at an obtuse angle to the major portion 20, and a rim 23 at an acute angle to the second flange 27.

[0029] A rectangular piece of sheet material, the blanket 26, and of course the major portion 20 of the carrier sheet C, have a longitudinal dimension approximately equal to the circumference of the cylinder assembly B minus the width of the entrance slot 6 of the undercut groove 7. As will be understood by referring back to FIG. 2, therefore, the blanket 26 is to be left wholly exposed on the surface of the cylinder assembly B when the blanket assembly T is mounted in position thereon.

[0030] It will also be observed from FIG. 2 that the first flange 21 of the carrier sheet C is at the upstream end of the blanket assembly T with respect to the predetermined rotational direction of the cylinder assembly B during printing, which is clockwise as indicated by the arrow in FIG. 2. At the downstream end, then, of the blanket assembly T are the rim 23 and the second flange 27 for engaging the retainer spindle 12 in the undercut groove 7. The angles of the flanges 21 and 27 relative to the major portion 20, and that of the rim 23 relative to the flange 27 will be later set forth in more detail in the course of the discussion of the undercut groove 7 in the cylinder assembly B and of the blanket retainer spindle 12 housed therein.

Cylinder Assembly

[0031] Referring back to FIG. 1, the cylinder assembly B comprises a body part 1 of cylindrical shape, and a

pair of aligned shafts 2 and 3, complete with collars 4 and 5, coaxially attached, as by pressfitting, to the opposite ends of the body part 1. The undercut groove 7 is cut eccentrically in the body part 1, extending parallel to its axis, and open at both ends to a pair of holes 10 and 11 in the collars 4 and 5. The outer ends of the holes 10 and 11 are closed with bearing plates 14 and 15 rotatably supporting the retainer spindle 12.

[0032] As drawn on an enlarged scale in FIG. 2, the undercut groove 7 is approximately teardrop-shaped in cross section, having the entrance slot 6 of minimal width cut in the surface of the body part 1, and a pair of walls 8 and 9 diverging apart as they extend away from the entrance slot. The entrance slot 6 is only as wide as somewhat more than twice the thickness of the carrier sheet C of the blanket assembly T.

[0033] Also as seen cross-sectionally as in FIG. 2, the entrance slot 6 is bounded by and between a first 24 and a second 25 longitudinal edge, which are defined in turn by the surface of the cylinder assembly body part 1 and the diverging inside walls 8 and 9 of the undercut groove 7. The first longitudinal edge 24 is to be engaged by the upstream end flange 21 of the blanket assembly T and so formed into approximately the same acute angle as that between the upstream end flange 21 and major portion 20 of the blanket assembly carrier sheet C. The second longitudinal edge 25 is to be temporarily engaged by the downstream end rim 23 of the blanket assembly T during the mounting of the blanket assembly to the cylinder assembly B. The angle of this second longitudinal edge 25 is more acute than the angle between the rim 23 and downstream end flange 27 of the blanket assembly T.

[0034] A study of FIG. 2 will further indicate the relative angles of the flanges 21 and 27 of the blanket assembly T with respect to its major portion 20. These angles should be so determined that when both flanges 21 and 27 are fully received in the undercut groove 7 as in this figure, or when the downstream end flange 27 is being inserted in the undercut groove following the insertion of the downstream end rim 23 (FIG. 4D), both flanges 21 and 27 are in parallel spaced relationship to each other or somewhat diverge apart from each other as they extend away from the entrance slot 6.

Blanket Retainer Spindle

[0035] As seen in both FIGS. 1 and 2, the retainer spindle 12 of generally cylindrical shape is rotatably received with clearance in the undercut groove 7 in the cylinder assembly body part 1. Further the retainer spindle 12 has a pair of reduced diameter extensions at its opposite ends, which are received with substantial clearance in the pair of aligned holes 10 and 11 in the collars 4 and 5, a pair of journals 40 of still more reduced diameter rotatably supported by the noted pair of bearing plates 14 and 15, and a pair of extensions 41 of hexagonal cross section projecting outwardly of the cylinder

assembly B.

[0036] Coiled around the reduced diameter extensions of the retainer spindle 12 are a pair of helical torsion springs 17 and 18 anchored each at one end to the retainer spindle 12 and at the other end to one of the bearing plates 14 and 15. The torsion springs 17 and 18 conjointly bias the retainer spindle 12 to turn counterclockwise, as viewed in FIG. 2, this being a direction necessary for holding the blanket assembly T firmly against the cylinder assembly B.

[0037] The pair of hexagonal extensions 41 projecting from the cylinder assembly B is for engagement by a spanner or wrench 19 in turning the retainer spindle 12 clockwise, again as viewed in FIG. 2, against the forces of the torsion springs 17 and 18. With the retainer spindle 12 so turned, the blanket assembly T is loosenable and dismountable from the cylinder assembly B. The turning tool 19 in combination with the hexagonal extensions 41 of the retainer spindle 12 constitute the dismounting means 13.

[0038] FIG. 2 best reveals that the retainer spindle 12 is recessed longitudinally to provide a pull-in hook 16 and a push-out ledge 28 which are spaced from, and opposed to, each other circumferentially of the retainer spindle. The pull-in hook 16 is to engage the rim 23 at the downstream end of the blanket assembly T for tightening the same around the cylinder assembly B with the clockwise rotation of the retainer spindle 12. It will be noted from this figure that the pull-in hook 16 is more acutely angled than the rim 23 is to the flange 27. The push-out ledge 28 is for movement, upon counterclockwise rotation of the retainer spindle 12 from its FIG. 2 position, into abutment against the rim 23 for pushing the same back toward the entrance slot 6 in dismounting the blanket assembly T.

[0039] The pull-in hook 16 and push-out ledge 28 should therefore be sufficiently spaced from each other not to interfere with each other's functioning. As will be understood, the hook 16 and ledge 28 need not be formed continuously throughout the length of the retainer spindle 12 but may be broken up into several discrete parts spaced longitudinally of the spindle.

Method of Blanket Mounting

[0040] The blanket assembly T may be mounted to the cylinder assembly B through the procedure of FIGS. 4A-4E. The mounting procedure starts with the full insertion, as in FIG. 4A, of the upstream end flange 21 of the blanket assembly T in the undercut groove 7 in the cylinder assembly body part 1, resulting in the positive engagement of this upstream end flange with the first longitudinal edge 24 of the undercut groove entrance slot 6.

[0041] FIG. 4A is also explanatory of the angular position of the retainer spindle 12 when the pair of torsion springs 17 and 18, FIG. 1, are not torsionally stressed. The retainer spindle 12 is now fully turned counterclock-

drawn

wise, with the pull-in hook 16 held spaced in that direction from the tip of the upstream end flange 21, as fully inserted in the undercut groove 7, of the blanket assembly T.

[0042] Then, following the full insertion of the upstream end flange 21 of the blanket assembly T in the undercut groove 7, the cylinder assembly B may be turned one complete revolution in a clockwise direction from its FIG. 4A position to that of FIG. 4B. The blanket assembly T will be wrapped around the cylinder assembly B upon complete revolution of the latter, with the downstream end portion 30 of the blanket assembly brought close to the undercut groove entrance slot 6.

[0043] Then the retainer spindle 12 may be turned clockwise from its FIG. 4A position to that of FIG. 4B, by means of the wrench 19, FIG. 1, thereby stressing the pair of torsion springs 17 and 18. The pull-in hook 16 of the retainer spindle 12 is now positioned some distance away from the upstream end flange 21 of the blanket assembly T received in the undercut groove 7. The retainer spindle 12 may be temporarily locked in this FIG. 4B position by any appropriate locking means, not shown, against the forces of the torsion springs 17 and 18.

[0044] Then the rim 23 of the blanket assembly T may be engaged with the second longitudinal edge 25 of the undercut groove entrance slot 6. Toward this end the downstream end portion 30 of the blanket assembly may be first positioned as indicated by the broken lines in FIG. 4B and, by-applying a force thereto in such a direction as to cause the flange 27 to buckle toward the cylinder assembly B, driven into the entrance slot 6, as indicated by the solid lines in the same figure. Despite the narrowness of the entrance slot 6, the rim 23 will relatively easily enter therein thanks to the greater angle between the rim and the downstream end flange 27 of the blanket assembly T than the angle of the second longitudinal edge 25 of the entrance slot.

[0045] Then, preparatory to insertion of the downstream end flange 27 in the undercut groove 7, the buckling of the flange may be removed by turning the same about the entrance slot edge 25 in a counterclockwise direction, as indicated by the arrow in FIG. 4B. Then the downstream end flange 27 may be pushed linearly into the undercut groove 7, as depicted in FIG. 4C, until the flange is received therein as far down as possible as in FIG. 4D. Now the blanket carrier major portion 20 may, or may not, be in contact with the surface of the cylinder assembly body part 1. The downstream end flange 27 will be admitted into the undercut groove 7 without frictional engagement with the upstream end flange 21 because they are so angled to the carrier sheet major portion 20 that, when both received in the undercut groove, they are parallel to each other or diverge apart as they extend away from the entrance slot 6.

[0046] Then the retainer spindle 12 may be unlocked and allowed to turn counterclockwise from its FIG. 4D position to its FIG. 4E position under the bias of the tor-

sion springs 17 and 18. In the course of this counterclockwise turn the retainer spindle 12 will positively engage the rim 23 of the blanket assembly T by its pull-in hook 16 and so subsequently pull its downstream end flange 27 deeper into the undercut groove 7. As is apparent from a comparison of FIGS. 4A and 4E, the retainer spindle 12 will be held sprung counterclockwise even after the flange 27 has been fully received in the undercut groove 7, holding in turn the blanket assembly T firmly wrapped around the cylinder assembly against the likelihood of slacking during printing.

Method of Blanket Dismounting

[0047] The blanket assembly T to be dismantled being in the state of FIG. 4E, the retainer spindle 12 may be wrenched clockwise from this position against the forces of the torsion springs 17 and 18. So turned, the retainer spindle 12 will disengage the blanket assembly rim 23 from its pull-in hook 16, as shown in FIG. 5A.

[0048] Then, as pictured in FIG. 5B, the push-out ledge 28 of the retainer spindle 12 will come into abutment against the blanket assembly rim 23 and, with the continued clockwise turn of the retainer spindle, push the rim toward the undercut groove entrance slot 6. Thus will the blanket assembly T come loose on the cylinder assembly B.

[0049] Then, with the blanket assembly T sufficiently loosened on the cylinder assembly B, the blanket assembly upstream end flange 21 may be manually withdrawn from the undercut groove 7, as depicted in FIG. 5C. Then the blanket assembly may be unwrapped from the cylinder assembly by turning the latter clockwise. Finally, the blanket assembly downstream end portion 30 may be withdrawn from the undercut groove through the reversal of the mounting procedure set forth in conjunction with FIGS. 4B and 4C.

[0050] Various departures from the exemplified blanket cylinder according to the present invention may be made in the practice of the invention in order to conform to design preferences or to the requirements of each specific application of the invention. For example, two or more undercut grooves, each with a retainer spindle mounted therein, may be formed at circumferential spacings on the blanket cylinder within the scope of the invention. It is therefore appropriate that the invention be construed broadly and in a manner consistent with the fair meaning or proper scope of the claims which follow.

Claims

1. A blanket cylinder for use in offset lithography in combination with blanket means (T) including a blanket (28) and a carrier sheet (C) therefor, the carrier sheet having a major portion (20) to which the blanket is attached, a first end portion bent at an

angle to the major portion to provide a first flange (21), and a second end portion (30) bent twofold to provide a second flange (27) at an angle to the major portion, and a rim (23) at an angle to the second flange, the blanket cylinder comprising a cylinder (B) having formed therein an undercut groove (7) extending parallel to an axis of the cylinder, the undercut groove having an entrance slot (6) bounded by and between a first (24) and a second (25) longitudinal edge, the first longitudinal edge, being cross-sectionally shaped to be engaged by the first flange (21) of the carrier sheet (C), and a retainer spindle (12) mounted in the undercut groove in the cylinder for bidirectional rotation therein, characterized in that the retainer spindle (12) is cross-sectionally shaped to include a pull-in hook (16) for engaging the rim (23) of the carrier sheet (C) in order to pull the second end portion (30) thereof into the undercut groove (7) with the rotation of the retainer spindle in a first direction, and a push-out ledge (28), circumferentially spaced from and opposed to the pull-in hook, for abutment against the rim (23) of the carrier sheet in order to push the second end portion (30) thereof out the undercut groove with the rotation of the retainer spindle in a second direction which is opposite to the first direction, and that the retainer spindle (12) is biased by resilient means (17, 18) to turn in the first direction relative to the cylinder (B), whereby the blanket means (T) can be held fast against the cylinder without the risk of slacking during printing, and the entrance slot (6) of the undercut groove (7) rendered as narrow as approximately twice the thickness of the carrier sheet (C) of the blanket means.

2. A blanket cylinder as claimed in claim 1, **characterized in that** the undercut groove (7) in the cylinder (B) is approximately teardrop-shaped in cross section, with the first longitudinal edge (24) of the entrance slot (6) acute-angled in cross section in order to be positively engaged by the first flange (21) of the carrier sheet (C) of the blanket means (T).

3. A blanket cylinder as claimed in claim 2, **characterized in that** the second longitudinal edge (25) of the entrance slot (6) is acute-angled in cross section in order to be temporarily positively engaged by the rim (23) of the carrier sheet (C) of the blanket means (T) preparatory to insertion of the second flange (27) thereof into the undercut groove (7).

4. A blanket cylinder as claimed in claim 3, **characterized in that** the second longitudinal edge (25) of the entrance slot (6) is more acutely angled than the angle between the second flange (27) and the major portion (20), or the angle between the rim (23) and the second flange (27), of the carrier sheet (C) of the blanket means (T).

5. A blanket cylinder as claimed in claim 1, **characterized in that** the resilient means comprises a pair of torsion springs (17 and 18) coiled respectively around a pair of opposite end portions of the retainer spindle (12).

6. A blanket cylinder as claimed in claim 1, **characterized in that** the retainer spindle (12) has at least one end (41) projecting from the cylinder and adapted to be turned in the second direction against the force of the resilient means (17, 18) by a hand tool (19).

7. A blanket cylinder as claimed in claim 1, **characterized in that** the first flange (21) of the carrier sheet (C) of the blanket means (T) is bent at an acute angle to the major portion (20) thereof, and the second flange (27) of the carrier sheet is bent at an obtuse angle to the major portion, and that the rim (23) is bent at an acute angle to the second flange.

8. A blanket cylinder as claimed in claim 7, **characterized in that** the sum of the acute angle between the first flange (21) and major portion (20) of the carrier sheet (C) and the obtuse angle between the second flange (27) and the major portion (20) is approximately 180 degrees.

9. A blanket cylinder as claimed in claim 7, **characterized in that** the first longitudinal edge (24) of the entrance slot (6) of the undercut groove (7) is cross-sectionally shaped into approximately the same acute angle as that between the first flange (21) and the major portion (20) of the carrier sheet (C).

10. A blanket cylinder as claimed in claim 7, **characterized in that** the second longitudinal edge (25) of the entrance slot (6) of the undercut groove (7) is cross-sectionally shaped into an acute angle that is less than the acute angle between the rim (23) and the second flange (27) of the carrier sheet (C).

— 6 —




FIG. 2




FIG. 3




FIG. 4A




FIG 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 5A




FIG. 5B





FIG. 5C





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 11 4549

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	DE 195 41 249 A (KOENIG & BAUER ALBERT AG) 7 November 1996 (1996-11-07)		B41F30/04
D	& PATENT ABSTRACTS OF JAPAN vol. 2000, no. 17, 5 June 2001 (2001-06-05) & JP 09 099543 A (KOENIG & BAUER ALBERT AG), 15 April 1997 (1997-04-15) * abstract *		
A	EP 0 844 082 A (KOENIG & BAUER ALBERT AG) 27 May 1998 (1998-05-27)		
D	& PATENT ABSTRACTS OF JAPAN vol. 2000, no. 17, 5 June 2001 (2001-06-05) & JP 07 060949 A (KOENIG & BAUER AG), 7 March 1995 (1995-03-07) * abstract *		
A	FR 2 341 434 A (MASCHF AUGSBURG NUERNBERG AG) 16 September 1977 (1977-09-16)		
A	DE 298 02 211 U (GOEBEL GMBH MASCHF) 9 April 1998 (1998-04-09)		TECHNICAL FIELDS SEARCHED (Int.Cl.7) B41F
A	EP 0 418 991 A (KOMORI PRINTING MACH) 27 March 1991 (1991-03-27)		
A	US 4 702 166 A (DEPA LOUIS S) 27 October 1987 (1987-10-27)		
A	US 5 454 316 A (OHTA HIDEO ET AL) 3 October 1995 (1995-10-03)		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 25 October 2001	Examiner DIAZ-MAROTO, V
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/02 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 11 4549

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-10-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19541249 A	07-11-1996	DE 29507523 U1	06-07-1995
		DE 19541249 A1	07-11-1996
		CH 691452 A5	31-07-2001
		FR 2733719 A1	08-11-1996
		GB 2300598 A, B	13-11-1996
		IT MI960844 A1	30-10-1997
		JP 9099543 A	15-04-1997
		US 5687648 A	18-11-1997
EP 0844082 A	27-05-1998	DE 4326250 A1	09-02-1995
		DE 9320590 U1	29-09-1994
		DE 59407724 D1	11-03-1999
		DE 59409719 D1	10-05-2001
		EP 0638420 A1	15-02-1995
		EP 0844082 A2	27-05-1998
		JP 2746839 B2	06-05-1998
		JP 7060949 A	07-03-1995
		US 5503072 A	02-04-1996
FR 2341434 A	16-09-1977	DE 2606223 A1	18-08-1977
		CH 614887 A5	28-12-1979
		DD 130319 A1	22-03-1978
		FR 2341434 A1	16-09-1977
DE 29802211 U	09-04-1998	DE 29802211 U1	09-04-1998
EP 0418991 A	27-03-1991	AT 135294 T	15-03-1996
		DE 69025835 D1	18-04-1996
		DE 69025835 T2	10-10-1996
		EP 0418991 A2	27-03-1991
		US 5131327 A	21-07-1992
US 4702166 A	27-10-1987	AU 574948 B2	14-07-1988
		AU 6907187 A	03-03-1988
		CA 1271368 A1	10-07-1990
		DE 3779011 D1	17-06-1992
		DE 257176 T1	30-06-1988
		EP 0257176 A2	02-03-1988
		JP 63057235 A	11-03-1988
		MX 169958 B	03-08-1993
US 5454316 A	03-10-1995	JP 2562413 B2	11-12-1996
		JP 7125180 A	16-05-1995

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

